
































Bases/fixations	Round support Infina	Concrete Anchorage	Infina base	Wheelset	Extra weight Infina	Granite base 50 kg	Granite base 80 kg	Lotus base
								
LxWxH cm	Ø22 x 40	Ø22, H = 35	60 x 60 x 1,5	-	60 x 60 x 0,9	53 x 53 x 7,5	67 x 67 x 7,5	70 x 55 x 0,13
LxWxH inch	Ø7.2"x 1'3.7"	Ø7.2" H = 1'1.8"	2' x 2' x 0.6"	-	2'x 2'x 0.35"	1'7"x 1'7" x 2.3"	2'2"x 2'2"x 2.3"	2'3.5"x 1'8"x 0.5"
Weight kg/lb product	2,9/6.4	4,5/9.9	40/88	-	20/44	50/110	80/176	26/57
LxWxH cm packaging	60 x 40 x 30	60 x 40 x 30	66 x 64 x 4	33 x 10 x 10	62 x 62 x 4	65,8 x 56 x 8,5	70 x 79,5 x 8,5	71 x 57 x 4
LxWxH inch packaging	1'9"x 1'3"x 1'	1'9"x 1'3"x 1'	2'2.2"x 2'1"x 1.6"	1'0.8"x 3.3"x 3.3"	2'0.4"x 2'0.4"x 1.6"	2'2.2"x 1'8.4"x 2.6"	2'3"x 2'6"x 2.6"	2'3"x 1'8.7"x 1.6"
Weight kg/lb packaging	3,8/8.4	4,8/10.58	40,5/89.3	1,5/3.3	25.5/56.2	53,2/117	83,7/183	26/57
Material	Galvanised steel	Galvanised steel	Galvanised steel - Top anodised aluminum 1 mm/0.04"		Galvanised steel 9 mm/0.35"	Granite	Granite	Galvanized steel with aluminum top
Good to know	Required for pole installation	Pit of 60 x 60 x 40 or 2"x 2"x 1'4" filled with concrete	Tube of Ø45/400 (Ø1'4.7"/13'1.2")	Infina / Granite base 50 kg and 80 kg				Movable base Rolls on nylon wheels
INFINA								
 R0 300/SQ250	•	•	•	•	•	•	•	
 R0 350/SQ300	•	•	•	•	•		•	
LEGNO								
 2,5 M						•	•	
 3,5 M							•	
BASIC								
 190/220/270						•	•	
 250/300							•	
LOTUS								
								•

The content of this document, in particular the mentioned models, is protected by copyrights and/or design rights. The present document and its content is communicated to you for information purposes only. Any partial or total reproduction or any other use without our prior written permission is strictly prohibited. This technical sheet remains subject to possible changes. Of course we do our best to eliminate all mistakes, but Umbrosa is not responsible for the errors in the documentation of products. All measurements are approximate and are provided for informational purposes only.

Bases/fixations	Round support 90°	Concrete Anchorage	Tile base	Stabilizers (Tile base)	Wheelset	Mobile base	Stabilizers (Mobile base)
							
LxWxH cm	Ø22, H = 50	Ø22, H = 35	85 x 85 x 15	-	-	80 x 80 x 8,5	-
LxWxH inch	Ø7.2" H = 1'6.4"	Ø7.2" H = 1'1.8"	2'7.8"x2'7.8"x 6"	-	-	2'2.6"x 2'2.6"x 2.8"	-
Weight kg/lb product	4/8.8	4,5/9.9	15,6/34.5 + 6/14	-	-	120/265	-
LxWxH cm packaging	60 x 40 x 30	60 x 40 x 30	86 x 86 x 17	32 x 25 x 4	33 x 10 x 10	85 x 29 x 9	32 x 25 x 4
LxWxH inch packaging	1'9"x 1'3"x 1'	1'9"x 1'3"x 1'	2'10"x 2'10"x 3.1"	1'0.4"x 8.2" x 1.3"	1'0.8"x 3.3"x 3.3"	2'7.8"x 9.5"x 3.5"	1'0.4"x 8.2" x 1.3"
Weight kg/lb packaging	4,3/9.4	4,8/10.58	15,95/35.1 + 6,38/14,6	4,6/10.14	1,5/3.3	3x 40/88	4,6/10.14
Material	Galvanised steel	Galvanised steel	Galvanised steel and anodized aluminum plate 1,5 mm	Galvanised steel		Concrete with surface finish	Galvanised steel
Good to know	Required for pole installation	Pit of 60 x 60 x 40 or 2' x 2' x 1'4" filled with concrete	Fill with 12 tiles 400 x 400 x 38 mm/16"x16"x2" - weight 178 kg/392lb		For Tile Base.	Easy manipulation with handle	
PARAFLEX							
	•	•	•	•	•	•	•
	•	•	•	•	•	•	•
	•	•		•			•
ICARUS							
	INCL	•	•	•	•		•
ECLIPSUM							
	INCL	•	•	•	•		•
SPECTRA							
	INCL	•	•	•	•	•	•
	INCL	•	•	•	•		•
	INCL	•	•	•	•		
	INCL	•		•			